



Principio di funzionamento Operating principle Принцип действия	Disegno Drawing Чертёж	N° Catalogo Part Number N° по каталогу	Tipo Bobina Coil Type Тип катушки (1)	Attacchi ODS Ø Connections ODS Ø Соединительные концы под пайку внахлест ODS Ø		Kv [m³/h] Kv [m³/ч]	PS [bar] PS [бар]	TS [°C]		Confezione n° pz Package pcs Упаковка, шт
				[in.]/ [дюйм]	[mm]			min мин	max макс	
Servocomando a pistone Piston pilot operated Поршневой исполнительный механизм		1058N/5A6	HF2	5/8"	16	3,80	45	-40	+120	14
		1058N/6A6		3/4"	-	4,80				
		1058N/7A6		7/8"	22	5,70				
		1059N/9A6		1.1/8"	-	5,70				
		1098N/9A6		1.1/8"	-	10	45	-40	+120	1
		1099N/11A6		1.3/8"	35	10				
		1078N/11A6		1.3/8"	35	16				
		1079N/13A6		1.5/8"	-	16				
		1079N/M42A6		-	42	16				
		1078N/13A6		1.5/8"	-	25				
		1078N/M42A6		-	42	25				
		1079N/17A6		2.1/8"	54	25				

(1) : bobine montate sulle valvole

(1) : coils mounted on the valves

(1) : катушки монтируются на клапанах

NB: Non impiegare con R22



NB: No use with R22

Примечание. Запрещено использовать с R22

VALVOLE SOLENOIDE PULSATE PER BY-PASS GAS CALDO E INIEZIONE DI LIQUIDO

PULSE SOLENOID VALVES FOR HOT GAS BY-PASS AND LIQUID INJECTION

ИМПУЛЬСНЫЕ ЭЛЕКТРОМАГНИТНЫЕ КЛАПАНЫ ДЛЯ ПЕРЕПУСКА ГОРЯЧЕГО ГАЗА И ВПРЫСКИВАНИЯ ЖИДКОСТИ

Principio di funzionamento Operating principle Принцип действия	Disegno Drawing Чертёж	N° Catalogo Part Number N° по каталогу	Tipo Bobina Coil Type Тип катушки (1)	Attacchi ODS Ø Connections ODS Ø Соединительные концы под пайку внахлест ODS Ø		Kv [m³/h] Kv [m³/ч]	PS [bar] PS [бар]	TS [°C]		Confezione n° pz Package pcs Упаковка, шт
				[in.]/ [дюйм]	[mm]			min мин	max макс	
Azione diretta Direct acting Прямое действие		1328N/2S020	HF2 HF3 HM2 HM3 HM4 CM2	1/4"	-	0,15	45	-40	+150	24
		1328N/2S030		1/4"	-	0,23				24
		1328N/3S020		3/8"	-	0,15				24
		1328N/3S030		3/8"	-	0,23				24
		1328N/M10S020		-	10	0,15				24
		1328N/M10S030		-	10	0,23				24
Servocomando a pistone Piston pilot operated Поршневой исполнительный механизм		1338N/3S065	HF2 HF3 HM2 HM3 HM4 CM2	3/8"	-	1,00	45	-40	+150	24
		1338N/M10S065		-	10					24
		1338N/M12S065		-	12					24
		1338N/4S065		1/2"	-					24

(1) : bobine che possono essere montate sulle valvole

(1) : coils that can be mounted on the valves

(1) : катушки, которые могут монтироваться на клапанах

NB: Non impiegare con R22

NB: No use with R22

Примечание. Запрещено использовать с R22