






Principio di funzionamento Operating principle Принцип действия	Disegno Drawing Чертеж	N° Catalogo Part Number N° по каталогу	Tipo Bobina Coil Type Тип катушки (1)	Attacchi ODS Ø Connections ODS Ø Соединительные концы под пайку внахлест ODS Ø		Kv [m³/h] Kv [м³/ч]	PS [bar] PS [бар]	TS [°C]		Confezione n° pz Package pcs Упаковка, шт
				[in.] / [дюйм]	[mm]			min мин	max макс	
Azione diretta Direct acting Прямое действие		1028N/2S	HF2 HF3 HM2 HM3 HM4 CM2	1/4"	-	0,15	45	-40	+130	24
		1028N/2S.E		1/4"	-	0,23				
		1028N/3S		3/8"	-	0,23				
		1028N/M10S		-	10	0,23				
Servocomando a membrana Diaphragm pilot operated Мембранный исполнительный механизм		1068N/3S	HF2 HF3 HM2 HM3 HM4 CM2	3/8"	-	0,80	45	-40	+120	24
		1068N/M10S		-	10					
		1068N/M12S		-	12					
		1068N/4S		1/2"	-					
		1078N/M12S		-	12	2,20	45	-40	+120	17
		1078N/4S		1/2"	-	2,20				
		1078N/5S		5/8"	16	2,61				
		1079N/7S		7/8"	22	2,61				
		1098N/5S		5/8"	16	3,80	45	-40	+120	14
		1098N/6S		3/4"	-	4,80				
		1098N/7S		7/8"	22	5,70				
		1099N/9S		1.1/8"	-	5,70				
		1078N/9S		1.1/8"	-	10,00	45	-40	+120	1
		1079N/11S		1.3/8"	35					

(1) : bobine che possono essere montate sulle valvole
(1) : coils that can be mounted on the valves
(1) : катушки, которые могут монтироваться на клапанах

NB: Non impiegare con R22
NB: No use with R22
Примечание. Запрещено использовать с R22