

Disegno Drawing Чертёж	N° catalogo Part number N° по каталогу	Attacchi Connections Соединительные концы			Kv [m³/h] Kv [м³/ч]	Pressione differenziale Differential pressure [bar] Избыточное давление [бар] (1)	PS [bar] PS [бар]	TS [°C]		Confezione n° pz Package pcs Упаковка, шт
		SAE Flare раз- вальц SAE	ODS / пайку ODS					min мин	max макс	
			Ø [in.]/ [дюйм]	Ø [mm]						

IN LINEA CON ATTACCHI SAE FLARE / STRAIGHT WITH SAE FLARE CONNECTIONS / ПРЯМЫЕ С СОЕДИНИТЕЛЬНЫМИ КОНЦАМИ ПОД РАЗВАЛЬЦОВКУ SAE

	3112W/2	1/4"	-	-	0.5	0.04	45	-40	+150	20
	3112W/3	3/8"			1.5					20
	3112W/4	1/2"			1.8					20
	3112W/5	5/8"			3.3					20
	3112W/6	3/4"			5					16
	3113W/2	1/4"			0.5	0.3				20
	3113W/3	3/8"			1.5					20
	3113W/4	1/2"			1.8					20
	3113W/5	5/8"			3.3					20
	3113W/6	3/4"			5					16

Valvole 3112/.., 3112N/.. in esaurimento scorte

Valves 3112/.., 3112N/.. running out of stock

Клапаны 3112/.., 3112N/.. заканчиваются на складе.

IN LINEA CON ATTACCHI ODS DI RAME / STRAIGHT WITH COPPER ODS CONNECTIONS / ПРЯМЫЕ С МЕДНЫМИ СОЕДИНИТЕЛЬНЫМИ КОНЦАМИ ODS

	3132W/2	-	1/4"	-	0.5	0.04	45	-40	+150	25
	3132W/3		3/8"	-	1.5					25
	3132W/M10		-	10	1.5					25
	3132W/M12		-	12	1.8					16
	3132W/4		1/2"	-	1.8					16
	3132W/5		5/8"	16	3.3					16
	3132W/M18		-	18	5					21
	3132W/6		3/4"	-	5					21
	3132W/7		7/8"	22	5					21
	3133W/2		1/4"	-	0.5	0.3				25
	3133W/3		3/8"	-	1.5					25
	3133W/M10		-	10	1.5					25
	3133W/M12		-	12	1.8					16
	3133W/4		1/2"	-	1.8					16
	3133W/5		5/8"	16	3.3					16
	3133W/M18		-	18	5					21
	3133W/6		3/4"	-	5					21
	3133W/7		7/8"	22	5					21

Valvole 3132/.., 3132N/.., 3133/.., 3133N/.. in esaurimento scorte

Valves 3132/.., 3132N/.., 3133/.., 3133N/.. running out of stock

Клапаны 3132/.., 3132N/.., 3133/.., 3133N/.. заканчиваются на складе.

(1) Minima pressione a cui la valvola è completamente aperta

(1) Minimum pressure at which the valve is completely open

(1): Минимальное давление, при котором клапан полностью открыт