

INDICATORI DI LIQUIDO
serie LI

LIQUID INDICATORS
LI series

Type	Type of connection	SAE Flare	ODS Ø		ODM Ø		For pipe Ø		TS [°C]	PS [bar]	Dimensions [mm]					Category 2014/68/EU PED	Weight [g]	Pieces per box						
			[in]	[mm]	[in]	[mm]	[in]	[mm]			ØD	L	H	H1	CH									
LI2MM	Male-male	1/4"	-	-	-	-	-	-	-40 ÷ +120	45	32	70	22,5	8	14	Art. 4.3	120	25						
LI3MM		3/8"	-	-	-	-	-	-				75	29,5	12	22		190	25						
LI4MM		1/2"	-	-	-	-	-	-				80					204	25						
LI5MM		5/8"	-	-	-	-	-	-				88	31,5	13	24		255	25						
LI6MM		3/4"	-	-	-	-	-	-				91	35,5	15	28		325	25						
LI2MF	Male-female	1/4"	-	-	-	-	-	-				70	29,5	12	22		209	25						
LI3MF		3/8"	-	-	-	-	-	-				75					202	25						
LI4MF		1/2"	-	-	-	-	-	-				80	31,5	13	24		235	25						
LI5MF		5/8"	-	-	-	-	-	-				85	35,5	15	28		305	25						
LI6MF		3/4"	-	-	-	-	-	-				94	41,5	17,5	35		471	25						
LI2SL	By-pass	-	-	-	1/4"	6	-	-				202	7	22,5	-		130	35						
LI2SLP		-	-	-	1/4"	6	-	-				98,5	38	58,5	-		130	32						
LI2S	Soldering	Hot forged brass	-	1/4"	-	-	-	-			36	125	22,5	8	14	Art. 4.3	126	50						
LI3S			-	3/8"	-	-	-	-									-	132	50					
LIM10S			-	-	10	-	-	-									-	133	50					
LIM12S			-	-	12	-	-	-									-	203	50					
LI4S			-	1/2"	-	-	-	-									-	132	29,5	12	22		205	50
LI5S			-	5/8"	16	-	-	-									-						198	50
LIM18S			-	-	18	-	-	-									-	145	31,5	13	24		235	50
LI6S			-	3/4"	-	-	-	-									-						237	50
LI7S			-	7/8"	22	-	-	-									-	155	35,5	15	28	309	42	
LI9S			-	1.1/8"	28	-	-	-									-	183	41,5	17,5	35	510	42	
LIM28SCU			-	-	-	-	28	-									-	150	30	-	235	228	26	
LI11S			-	-	-	1.3/8"	35	-									-	160	33,5	-	-	275	26	
LI11ST	-	1.3/8"	35	-	-	-	-	-				-	283	26										
LI13S	Copper tube	-	-	-	1.5/8"	-	-	-	170	37		-	-	Cat. I	425	26								
LI13ST		-	1.5/8"	-	-	-	-	-				-	-		425	26								
LIM42S		-	-	-	-	42	-	-				-	-		425	26								
LI17ST		-	2.1/8	54	-	-	-	-				43	-		-	540	26							
LI5T	Saddle	-	-	-	-	-	5/8"	16	-	36		-	32	Excluded	120	25								
LIM18T		-	-	-	-	-	-	18	-	37		-			120	25								
LI7T		-	-	-	-	-	7/8"	22	-	39		-			120	25								
LI9T		-	-	-	-	-	1.1/8"	28	-	42		-			120	25								
LI11T		-	-	-	-	-	1.3/8"	35	-	45		-			120	25								
LIM42T		-	-	-	-	-	1.5/8"	42	-	48,5		-			120	25								
LI17T		-	-	-	-	-	2.1/8"	54	-	56		-			120	25								

