





Principio di funzionamento Operating principle Принцип действия	Disegno Drawing Чертёж	N° Catalogo Part Number N° по каталогу	Tipo Bobina Coil Type Тип катушки (1)	Attacchi ODS Ø Connections ODS Ø Соединительные концы под пайку внахлест ODS Ø		Kv [m³/h] Kv [м³/ч]	PS [bar] PS [бар]	TS [°C]		Confezione n° pz Package pcs Упаковка, шт
				[in.]/ [дюйм]	[mm]			min мин	max макс	
Servocomando a pistone Piston pilot operated Поршневой исполнительный механизм		1038/3S	HF2 HF3 HM2 HM3 HM4 CM2	3/8"	-	1,00	45	-35	+110	24
		1038/M10S		-	10					
		1038/M12S		-	12					
		1038/4S		1/2"	-					
		1048/M12S		-	12	2,40	45	-35	+110	14
		1048/4S		1/2"	-					
		1048/5S		5/8"	16	3,00				
		1049/7S		7/8"	22					
		1058/5S		5/8"	16	3,80	45	-35	+110	14
		1058/6S		3/4"	-	4,80				
		1058/7S		7/8"	22	5,70				
		1059/9S		1.1/8"	-					
		1098/9S		1.1/8"	-	10	45	-35	+110	1
		1099/11S		1.3/8"	35					
		1078/11S		1.3/8"	35	16				
		1079/13S		1.5/8"	-					
		1079/M42S		-	42					
		1078/13S		1.5/8"	-	25				
		1078/M42S		-	42					
		1079/17S		2.1/8"	54					

(1) : bobine che possono essere montate sulle valvole

(1) : coils that can be mounted on the valves

(1) : катушки, которые могут монтироваться на клапанах