



Disegno Drawing Чертёж	N° catalogo Part number N° по каталогу	Attacchi Connections Соединительные концы				Kv [m³/h]	Pressione differenziale Differential pressure [bar] Избыточное давление [бар] (1)	PS [bar] PS [бар]	TS [°C]		Confezione n° pz Package pcs Упаковка, шт
		SAE Flare раз- вальц SAE	ODS / пайку ODS		ODM / пайку ODM						
			Ø [in.]/ [дюйм]	Ø [mm]	Ø [in.]/ [дюйм]	Ø [mm]			min мин	max макс	

IN LINEA CON ATTACCHI ODS D'OTTONE / STRAIGHT WITH BRASS ODS CONNECTIONS / ПРЯМЫЕ С ЛАТУННЫМИ СОЕДИНИТЕЛЬНЫМИ КОНЦАМИ ПОД ПАЙКУ
ВНАХЛЕСТ ODS

	3122/M22	-	-	22	-	28	6.6	0.1	45	-35	+160	14
	3122/7		7/8"	-	1.1/8"	-	6.6					14
	3122/M28		-	28	1.3/8"	35	8.8					14
	3122/9		1.1/8"	-	1.3/8"	35	8.8					14
	3122/11		1.3/8"	35	1.5/8"	-	15.2					1
	3122/13		1.5/8"	-	2"	-	25					1
	3122/M42		-	42	2"	-	25					1
	3122/17		2.1/8"	54	-	-	40					1
	3124N/M22 (2)	-	-	22	-	28	8.1	0.04	45	-40	+150	14
	3124N/7 (2)		7/8"	-	1.1/8"	-	8.1					14
	3124N/M28 (2)		-	28	1.3/8"	35	10.4					14
	3124N/9 (2)		1.1/8"	-	1.3/8"	35	10.4					14
	3124N/11 (2)		1.3/8"	35	1.5/8"	-	15.6					14
	3124N/13 (2)		1.5/8"	-	2"	-	27					1
	3124N/M42 (2)		-	42	2"	-	27					1
	3124N/17 (2)		2.1/8"	54	-	-	39					1
	3125N/M22 (2)		-	22	-	28	8.1	0.3				14
	3125N/7 (2)		7/8"	-	1.1/8"	-	8.1					14
	3125N/M28 (2)		-	28	1.3/8"	35	10.4					14
	3125N/9 (2)		1.1/8"	-	1.3/8"	35	10.4					14
	3125N/11 (2)		1.3/8"	35	1.5/8"	-	15.6					14
	3125/13 (2)		1.5/8"	-	2"	-	27					1
	3125/M42 (2)		-	42	2"	-	27					1
	3125/17 (2)		2.1/8"	54	-	-	39					1

(1) Minima pressione a cui la valvola è completamente aperta

(1) Minimum pressure at which the valve is completely open

(1): Минимальное давление, при котором клапан полностью открыт

(2) Non impiegare con R22

(2) No use with R22

(2) Запрещено использовать с R22