








Principio di funzionamento Operating principle Принцип действия	Disegno Drawing Чертеж	N° Catalogo Part Number N° по каталогу	Tipo Bobina Coil Type Тип катушки (1)	Attacchi ODS Ø Connections ODS Ø Соединительные концы под пайку внахлест ODS Ø		Kv [m³/h] Kv [m³/h]	PS [bar] PS [bar]	TS [°C] min max		Confezione n° pz Package pcs Упаковка, шт
				[in.]/ [дюйм]	[mm]					
Azione diretta Direct acting Прямое действие		1028N/2A6	HF2	1/4"	-	0,15	45	-40	+130	24
		1028N/2A6.E		1/4"	-	0,23				
		1028N/3A6		3/8"	-	0,23				
		1028N/M10A6		-	10	0,23				
Servocomando a membrana Diaphragm pilot operated Мембранный исполнительный механизм		1068N/3A6	HF2	3/8"	-	0,80	45	-40	+120	24
		1068N/M10A6		-	10					
		1068N/M12A6		-	12					
		1068N/4A6		1/2"	-					
		1078N/M12A6		-	12	2,20	45	-40	+120	17
		1078N/4A6		1/2"	-	2,20				
		1078N/5A6		5/8"	16	2,61				
		1079N/7A6		7/8"	22	2,61				
		1098N/5A6		5/8"	16	3,80	45	-40	+120	14
		1098N/6A6		3/4"	-	4,80				
		1098N/7A6		7/8"	22	5,70				
		1099N/9A6		1.1/8"	-	5,70				
		1078N/9A6		1.1/8"	-	10,00	45	-40	+120	1
		1079N/11A6		1.3/8"	35					
Servocomando a pistone Piston pilot operated Поршневой исполнительный механизм		1038N/3A6	HF2	3/8"	-	1,00	45	-40	+120	24
		1038N/M10A6		-	10					
		1038N/M12A6		-	12					17
		1038N/4A6		1/2"	-					
		1048N/M12A6		-	12	2,40	45	-40	+120	14
		1048N/4A6		1/2"	-	2,40				
		1048N/5A6		5/8"	16	3,00				
		1049N/7A6		7/8"	22	3,00				

(1) : bobine montate sulle valvole
(1) : coils mounted on the valves
(1): катушки монтируются на
клапанах

NB: Non impiegare con R22
NB: No use with R22
Примечание. Запрещено
использовать с R22