

VALVOLE DI RITEGNO, IN LINEA CON ATTACCHI ODS D'OTTONE
CHECK VALVES, STRAIGHT WITH BRASS ODS CONNECTIONS
CLAPETS ANTI-RETOUR, CONNEXIONS DROITES ODS LAITON
RÜCKSCHLAGVENTILE, DURCHFLUSS VERBINDUNG ODS MESSING

Disegno Drawing Dessin Zeichnung	N° Catalogo Part Number N° Catalogue Katalog Nr	Attacchi Connections Raccords Anschlüsse				Kv [m³/h]	pressione differenziale differential pressure Pression différentielle Differenzial Druck	PS [bar]	TS [°C]		Confezione n° pz Package pcs Emballage Verpackung
		ODS		ODM			(1)		min.	max.	
		Ø [in.]	Ø [mm]	Ø [in.]	Ø [mm]		[bar]				
	3124N/M22	-	22	-	28	8,1	0,04	50	-40	+150	14
	3124N/7	7/8"	-	1.1/8"	-						
	3124N/M28	-	28	1.3/8"	35	10,4					
	3124N/9	1.1/8"	-								
	3124N/11	1.3/8"	35	1.5/8"	-	15,6					
	3124N/13	1.5/8"	-	2"		27					
	3124N/M42	-	42								
	3124N/17	2.1/8"	54	-		39					
	3125N/M22	-	22	28	8,1	0,3	50	-40	+150	14	
	3125N/7	7/8"	-								1.1/8"
	3125N/M28	-	28	1.3/8"	35						10,4
	3125N/9	1.1/8"	-								
	3125N/11	1.3/8"	35	1.5/8"	-					15,6	
	3125N/13	1.5/8"	-	2"						27	
	3125N/M42	-	42								
	3125N/17	2.1/8"	54	-						39	

(1) Minima pressione a cui la valvola è completamente aperta

(1) Minimum pressure at which the valve is completely open

(1) Pression minimale à laquelle la vanne est entièrement ouverte

1) Mindestdruck, bei dem das Ventil vollständig offen ist