



Disegno Drawing Чертёж	N° catalogo Part number N° по каталогу	Attacchi Connections Соединительные концы			Campo di regolazione Regulation range [bar] Диапазон регулирования давления [бар]	Kv [m³/h] Kv [м³/ч]	PS [bar] PS [бар]	TS [°C]		Confezione n° pz Package pcs Упаковка, шт
		SAE Flare раз-вальц SAE	ODS [in.]/[дюйм]	ODS [mm]				min мин	max макс	
	3340/4	1/2"	-	-	3-20	2,7	28 (1)	- 40	+ 110	15
	3340/5	5/8"	-	-						15
	3340/M12S	-	-	12	3-20	2,7	28 (1)	- 40	+ 110	15
	3340/4S	-	1/2"	-						15
	3340/5S	-	5/8"	16						15
	3340/7S	-	7/8"	22		8				
	3340/9S	-	1.1/8"	-		1				
	3340/M28S	-	-	28		1				
	3340/11S	-	1.3/8"	35	18 - 30	2,7	45	- 40	+ 110	1
	3345/M12S (2)	-	-	12						15
	3345/4S (2)	-	1/2"	-						15
	3345/5S (2)	-	5/8"	16						15
	3345/7S (2)	-	7/8"	22						8

Note:

(1): MWP = 405 psi in conformità a omologazione UL

(1): MWP = 405 psi according to UL approval

Примечание.

(1): Максимальное рабочее давление = 405 psi соответствует значению, одобренному UL.

(2): non omologato UL

(2): not UL approved

(2). не UL утвержден