



Disegno Drawing Чертёж	N° catalogo Part number № по каталогу	Attacchi Connections Соединитель- ные концы		Pressione statica Static pressure [bar] Статическое давление [бар]	Pressione operativa Working pressure [bar] Рабочее давление [бар]	PS [bar] PS [бар]	TS [°C]		Utilizzo Use использова- ние	Confezione n° pz Package pcs Упаковка, шт
		SAE Flare / развальцовку SAE					min мин	max макс		
		M	F							

MECCANISMI VALVOLA / SPARE VALVE CORES / МЕХАНИЗМ КЛАПАНА

	8394/B (1)	-	-	35	30	-	-30	+90	R22 HFC (4)	100
	8395/A1 (2)	-	-	90	50	-	-32	+100	R22 HFC (4) HFO (5)	100
	8395/A3 (2) (3)	-	-	90	50	-	-25	+130	HFC (4) HFO (5) R290, R600, R600a	100
	8395/A4 (2)	-	-	140	80	-	-35	+120	R744	100

Note:

- (1) Molla interna
(2) Molla esterna
(3) NB: Non impiegare con R22






Примечания.

- (1) Механизм включает внутреннюю пружину.
(2) Механизм включает наружную пружину.
(3) Примечание. Запрещено использовать с R22

- (4) : R134a, R32, R404A, R407C, R410A, R507
(5) : R1234yf, R1234ze, R448A, R449A, R450A, R452A

- (1) Inside spring
(2) Outside spring
(3) NB: No use with R22

COLLETTORI CON ATTACCHI DI CARICA / MANIFOLDS WITH ACCESS FITTINGS / КОЛЛЕКТОР С СЕРВИСНЫМИ КЛАПАНАМИ

	9900/X47	1/4"	-	-	-	45	-	-	-	1
	9900/X87	1/4"	-	-	-	45	-	-	-	1
	9900/X81	1/4"	-	-	-	45	-	-	-	1
	9901/X43 N	1/4"	-	-	-	120	-	-	-	1
	9901/X44 N	1/4"	-	-	-	120	-	-	-	1