



ТАБЛИЦА 4. Общие характеристики адаптеров

ТАБЛИЦА 4. Общие характеристики адаптеров													
Общий вид	Номер детали на рисунке	Номер по каталогу	Соединения			p_s [бар]	Размеры [мм]					Момент затяжки минимальный/максимальный [Н · м]	Масса [г]
			под вальцовку SAE [дюйм]	под пайку ODS			L_1	L_2	L_3	L_4	Ch		
				[дюйм]	[мм]								
Деталь 1  Деталь 2  Деталь 3 	1	9900/X58	1/4	1/4	—	45	—	—	16,0	12,5	17	11/14	67
	2	9900/X62					21,0	3,5	—	—	—	—	
	3	7580/2					—					—	
	1	9900/X58	1/4	—	6		—	—	16,0	12,5	17	11/14	83
	2	9900/X70					21,0	3,5	—	—	—	—	
	3	7580/2					—					—	
	1	9900/X59	3/8	3/8	—		—	—	18,5	14,7	22	20/25	114
	2	9900/X63					23,5	4,0	—	—	—	—	
	3	7580/3					—					—	
	1	9900/X59	3/8	—	10		—	—	18,5	14,7	22	20/25	130
	2	9900/X71					23,5	4,0	—	—	—	—	
	3	7580/3					—					—	
	1	9900/X60	1/2	1/2	—		—	—	21,0	17,0	27	34/47	207
	2	9900/X64					26,0	4,5	—	—	—	—	
	3	7580/4					—					—	
	1	9900/X60	1/2	—	12		—	—	21,0	17,0	27	34/47	226
	2	9900/X72					26,0	4,5	—	—	—	—	
	3	7580/4					—					—	
	1	9900/X61	5/8	5/8	16		—	—	22,5	18,0	30	54/75	271
	2	9900/X65					27,5	5,0	—	—	—	—	
	3	7580/5					—					—	
	1	9900/X68	3/4	3/4	—		—	—	25,0	20,0	36	68/71	404
	2	9900/X69					30,0	5,0	—	—	—	—	
	3	7580/6					—					—	
	1	9900/X68	3/4	—	18		—	—	25,0	20,0	36	68/71	455
	2	9900/X77					30,0	5,0	—	—	—	—	
	3	7580/6					—					—	

Адаптер под вальцовку / под пайку ODS

