



**ТАБЛИЦА 5. Общие характеристики колен**

Общий вид	Номер по каталогу	Международное обозначение	Соединения			$p_s$ [бар]	Размеры [мм]		Масса [г]
			под вальцовку SAE [дюйм]		NPT [дюйм]		H	L	
			Внешняя резьба	Внутренняя резьба					


**Колена под вальцовку SAE**

	7210/2	E2-4	1/4	—	—	45	24,5	24,5	26
	7210/3	E2-6	3/8				29,5	29,5	49
	7210/4	E2-8	1/2				32,5	32,5	83
	7210/5	E2-10	5/8				36,0	36,0	116
	7210/6	E2-12	3/4				42,5	42,5	192


**Колена под вальцовку SAE/NPT**

	7220/2	E1-4B	1/4	—	1/4	45	26,0	24,0	33
	7220/3	E1-6C	3/8		3/8		29,5	28,5	54
	7220/4	E1-8D	1/2		1/2		32,5	32,0	91
	7220/6	E1-12F	3/4		3/4		42,5	39,5	183

**Колена под вальцовку SAE / уменьшенный порт NPT**

	7230/21	E1-4A	1/4	—	1/8	45	24,5	23,5	25
	7230/32	E1-6B	3/8		1/4		29,5	29,5	46
	7230/43	E1-8C	1/2		3/8		32,5	31,0	75
	7230/54	E1-10D	5/8		1/2		36,0	35,0	114

**Колена под вальцовку SAE с внешней/внутренней резьбой**

	7240/2	—	1/4	1/4	—	45	28,5	28,0	56
	7240/3		3/8	3/8			32,0	31,0	84
	7240/4		1/2	1/2			39,5	38,0	198