

INDICATORI DI LIQUIDO - OMOLOGATI DA UNDERWRITERS LABORATORIES INC.
 LIQUID INDICATORS - APPROVED BY UNDERWRITERS LABORATORIES INC.
 ИНДИКАТОРЫ ЖИДКОСТИ, УТВЕРЖДЕННЫЕ UNDERWRITERS LABORATORIES INC.

Disegno Drawing Чертеж	N° catalogo Part number N° по каталогу	Attacchi Connections Соединительные концы			PS [bar] PS [бар]	TS [°C]		Confezione n° pz Package pcs Упаковка, шт
		SAE Flare / развальцов- ку SAE	ODS [in.] / [дюйм]	ODS [mm]		min мин	max макс	

ATTACCHI SAE FLARE MASCHIO - MASCHIO / SAE FLARE MALE - MALE CONNECTIONS / СОЕДИНИТЕЛЬНЫЕ КОНЦЫ ПОД РАЗВАЛЬЦОВКУ SAE ДЛЯ СОЕДИНЕНИЯ НАРУЖНОГО - НАРУЖНОГО

	3810/22	1/4"	-	-	45 (1)	-40	+120	20
	3810/33	3/8"						
	3810/44	1/2"						
	3810/55	5/8"						
	3810/66	3/4"						

ATTACCHI SAE FLARE MASCHIO - FEMMINA / SAE FLARE MALE - FEMALE CONNECTIONS / СОЕДИНИТЕЛЬНЫЕ КОНЦЫ ПОД РАЗВАЛЬЦОВКУ SAE ДЛЯ СОЕДИНЕНИЯ НАРУЖНОГО - ВНУТРЕННЕГО

	3850/22	1/4"	-	-	45 (1)	-40	+120	20
	3850/33	3/8"						20
	3850/44	1/2"						20
	3850/55	5/8"						20
	3850/66	3/4"						25

ATTACCHI DI RAME A SALDARE / COPPER BRAZE CONNECTIONS / МЕДНЫЕ СОЕДИНИТЕЛЬНЫЕ КОНЦЫ ПОД ПАЙКУ

	3840/2	-	1/4"	-	45 (1)	-40	+120	25
	3840/3		3/8"	-				25
	3840/M10		-	10				25
	3840/M12		-	12				25
	3840/4		1/2"	-				25
	3840/5		5/8"	16				16
	3840/M18		-	18				16
	3840/6		3/4"	-				16
	3840/7		7/8"	22				21
	3840/9		1.1/8"	-				16

Note:

(1): MWP = 500 psi in conformità a omologazione UL

(1): MWP = 500 psi according to UL approval

Примечание.

(1): Максимальное рабочее давление = 500 psi соответствует значению, одобренному UL.