


Disegno Drawing Чертёж	N° catalogo Part number N° по каталогу	Attacchi Connections Соединительные концы			PS [bar] PS [бар]	TS [°C]		Confezione n° pz Package pcs Упаковка, шт
		SAE Flare / развальцовку SAE	ODS / пайку внахлест ODS			min мин	max макс	
			Ø [in.]/[дюйм]	Ø [mm]				


ATTACCHI SAE FLARE MASCHIO - MASCHIO / SAE FLARE MALE - MALE CONNECTIONS / СОЕДИНИТЕЛЬНЫЕ КОНЦЫ ПОД РАЗВАЛЬЦОВКУ SAE ДЛЯ СОЕДИНЕНИЯ НАРУЖНОГО - НАРУЖНОГО

	3910/22	1/4"	-	-	45 (1)	-40	+120	20
	3910/33	3/8"						
	3910/44	1/2"						
	3910/55	5/8"						
	3910/66	3/4"						

ATTACCHI SAE FLARE MASCHIO - FEMMINA / SAE FLARE MALE - FEMALE CONNECTIONS / СОЕДИНИТЕЛЬНЫЕ КОНЦЫ ПОД РАЗВАЛЬЦОВКУ SAE ДЛЯ СОЕДИНЕНИЯ НАРУЖНОГО - ВНУТРЕННЕГО

	3950/22	1/4"	-	-	45 (1)	-40	+120	20
	3950/33	3/8"						20
	3950/44	1/2"						20
	3950/55	5/8"						20
	3950/66	3/4"						25

ATTACCHI DI RAME A SILDARE / COPPER BRAZE CONNECTIONS / МЕДНЫЕ СОЕДИНИТЕЛЬНЫЕ КОНЦЫ ПОД ПАЙКУ

	3940/2	-	1/4"	-	45 (1)	-40	+120	25
	3940/3		3/8"	-				25
	3940/M10		-	10				25
	3940/M12		-	12				25
	3940/4		1/2"	-				25
	3940/5		5/8"	16				16
	3940/M18		-	18				16
	3940/6		3/4"	-				16
	3940/7		7/8"	22				21
	3940/9		1.1/8"	-				16

Note:

(1): MWP = 500 psi in conformità a omologazione UL

(1): MWP = 500 psi according to UL approval

Примечание.

(1): Максимальное рабочее давление = 500 psi соответствует значению, одобренному UL.