


Disegno Drawing Чертеж	N° Catalogo Part Number № по каталогу	Attacchi Connections Соединения		Foro Sfera Ø Ball port Ø Ø проходного отверстия [mm]	Kv [m³/h]	PS [bar]	TS [°C]		Confezione n° pz Package pcs Кол-во штук в упаковке
		ODS / пайку ODS					Min / мин.	Max / макс.	
		Ø [in.] / [дюйм]	Ø [mm]						
	6570/M6A	—	6	10	0,8	45 (1)	-40	+150	25
	6570/2A	1/4"	—	10	0,8				25
	6570/3A	3/8"	—	10	3				25
	6570/M10A	—	10	10	3				25
	6570/M12A	—	12	10	5				25
	6570/4A	1/2"	—	10	5				25
	6570/M15A	—	15	15	17				16
	6570/5A	5/8"	16	15	17				16
	6570/M18A	—	18	15	17				16
	6570/6A	3/4"	—	15	17				16
	6570/7A	7/8"	22	19	29				21
	6570/M28A	—	28	25	51				16
	6570/9A	1.1/8"	—	25	51				16
	6590/11A	1.3/8"	35	32	86	45 (1)	-40	+150	5
	6590/13A	1.5/8"	—	38	117				10
	6590/M42A	—	42	38	117				10
	6590/17A	2.1/8"	54	50	214				1
	6591/M64A	—	64	50	214				1
	6591/21A	2.5/8"	—	50	214				1
	6570/M64A (2)	—	64	60	380				45
	6570/21A (2)	2.5/8"	—	60	380	1			
	6571/24A (2)	3"	76	60	380	1			
	6571/25A (2)	3.1/8"	80	60	380	1			
	6570/24A (2)	3"	76	73	550	1			
	6570/25A (2)	3.1/8"	80	73	550	1			
	6571/28A (2)	3.1/2"	89	73	550	1			
	6571/29A (2)	3.5/8"	92	73	550	1			
	6570/28A (2)	3.1/2"	89	82	710	1			
	6570/29A (2)	3.5/8"	92	82	710	1			
	6571/33A (2)	4.1/8"	105	82	660	1			
	6571/34A (2)	4.1/4"	108	82	660	1			

Note:

(1): MWP = 500 psi per 6570/.. e 6590/.. - MWP = 435 psi per 6571/.. e 6591/.. in conformità a omologazione UL

(1): MWP = 500 psi for 6570/.. and 6590/.. - MWP = 435 psi for 6571/.. and 6591/.. according to UL approval

(1): Максимальное рабочее давление = 500 psi для 6570/.. и 6590/.., максимальное рабочее давление = 435 psi для 6571/.. и 6591/.. соответствуют значениям, одобренным UL

(2): non omologato UL

(2): not UL approved

(2): не UL утвержден