





Principio di funzionamento Operating principle Принцип действия	Disegno Drawing Чертеж	N° Catalogo Part Number № по каталогу	Tipo Bobina Coil Type Тип катушки (1)	Attacchi ODS Ø Connections ODS Ø Соединительные концы под пайку внахлест ODS Ø		Kv [m³/h]	PS [bar]	TS [°C]		Confezione n° pz Package pcs Упаковка, шт
				[in.]/ [дюйм]	[mm]			min мин	max макс	
Servocomando a pistone Piston pilot operated Поршневой исполнительный механизм		1038N/3S	HF2 HF3 HM2 HM3 HM4 CM2	3/8"	-	1,00	45	-40	+120	24
		1038N/M10S		-	10					
		1038N/M12S		-	12					
		1038N/4S		1/2"	-					
		1048N/M12S		-	12	2,40	45	-40	+120	14
		1048N/4S		1/2"	-	2,40				
		1048N/5S		5/8"	16	3,00				
		1049N/7S		7/8"	22	3,00				
		1058N/5S		5/8"	16	3,80	45	-40	+120	14
		1058N/6S		3/4"	-	4,80				
		1058N/7S		7/8"	22	5,70				
		1059N/9S		1.1/8"	-	5,70				
		1098N/9S		1.1/8"	-	10	45	-40	+120	1
		1099N/11S		1.3/8"	35	10				
		1078N/11S		1.3/8"	35	16				
		1079N/13S		1.5/8"	-	16				
		1079N/M42S		-	42	16				
		1078N/13S		1.5/8"	-	25				
		1078N/M42S		-	42	25				
		1079N/17S		2.1/8"	54	25				

(1) : bobine che possono essere montate sulle valvole
(1) : coils that can be mounted on the valves
(1) : катушки, которые могут монтироваться на клапанах

NB: Non impiegare con R22
NB: No use with R22
Примечание. Запрещено использовать с R22