



Disegno Drawing Чертеж	N° catalogo Part number N° по каталогу	Attacchi Connections Соединительные концы				Kv [m³/h]	Pressione differenziale Differential pressure [bar]	PS [bar]	TS [°C]		Confezione n° pz Package pcs Кол-во штук в упаковке
		SAE Flare	ODS / пайку ODS		ODM / пайку ODM						
			Ø [in.] / [дюйм]	Ø [mm]	Ø [in.] / [дюйм]	Ø [mm]			Избыточное давление [бар] (1)	Min / мин.	

IN LINEA CON ATTACCHI ODS DI RAME / STRAIGHT WITH COPPER ODS CONNECTIONS / ПРЯМЫЕ С МЕДНЫМИ СОЕДИНИТЕЛЬНЫМИ КОНЦАМИ ПОД ПАЙКУ ВНАХЛЕСТ ODS

	3142/7	-	7/8"	22	-	-	6.6	0.1	45	-35	+150	15
	3142/M28		-	28			8.8					15
	3142/9		1.1/8"	-			8.8					15
	3142/11		1.3/8"	35			15.2					10
	3142/13		1.5/8"	-			25					1
	3142/M42		-	42			25					1
	3142/17		2.1/8"	54			40					1
	3142/21		2.5/8"	-			40					1
	3142/25		3.1/8"	-			40					1

A SQUADRA CON ATTACCHI ODS DI RAME / RIGHT ANGLE WITH COPPER ODS CONNECTIONS / ПРЯМОУГОЛЬНЫЕ С МЕДНЫМИ СОЕДИНИТЕЛЬНЫМИ КОНЦАМИ ПОД ПАЙКУ ВНАХЛЕСТ ODS

	3182/7 (2)	-	7/8"	22	-	-	8.5	0.1	45	-35	+150	10
	3182/M28 (2)		-	28			9.5					10
	3182/9 (2)		1.1/8"	-			9.5					10
	3182/11 (2)		1.3/8"	35			19					1
	3182/13		1.5/8"	-			37					1
	3182/M42		-	42			37					1
	3182/17		2.1/8"	54			45.4					1

(1): minima pressione a cui la valvola è completamente aperta
(1): minimum pressure at which the valve is completely open.
(1) Минимальное давление, при котором клапан полностью открыт

(2) Prodotto in esaurimento scorte
(2) Product running out of stock
(2) Изделия на складе отсутствуют